



Jet Noise Predictions Based on Two Different Forms of Lilley's Equation

Part 1: Basic Theory

Marvin E. Goldstein
Glenn Research Center, Cleveland, Ohio

Abbas Khavaran
QSS Group, Inc., Cleveland, Ohio

Ricardo E. Musafir
Federal University of Rio de Janeiro, Rio de Janeiro, Brazil

The NASA STI Program Office . . . in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) Program Office plays a key part in helping NASA maintain this important role.

The NASA STI Program Office is operated by Langley Research Center, the Lead Center for NASA's scientific and technical information. The NASA STI Program Office provides access to the NASA STI Database, the largest collection of aeronautical and space science STI in the world. The Program Office is also NASA's institutional mechanism for disseminating the results of its research and development activities. These results are published by NASA in the NASA STI Report Series, which includes the following report types:

- **TECHNICAL PUBLICATION.** Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA's counterpart of peer-reviewed formal professional papers but has less stringent limitations on manuscript length and extent of graphic presentations.
- **TECHNICAL MEMORANDUM.** Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- **CONTRACTOR REPORT.** Scientific and technical findings by NASA-sponsored contractors and grantees.

- **CONFERENCE PUBLICATION.** Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or cosponsored by NASA.
- **SPECIAL PUBLICATION.** Scientific, technical, or historical information from NASA programs, projects, and missions, often concerned with subjects having substantial public interest.
- **TECHNICAL TRANSLATION.** English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services that complement the STI Program Office's diverse offerings include creating custom thesauri, building customized databases, organizing and publishing research results . . . even providing videos.

For more information about the NASA STI Program Office, see the following:

- Access the NASA STI Program Home Page at <http://www.sti.nasa.gov>
- E-mail your question via the Internet to help@sti.nasa.gov
- Fax your question to the NASA Access Help Desk at 301-621-0134
- Telephone the NASA Access Help Desk at 301-621-0390
- Write to:
NASA Access Help Desk
NASA Center for Aerospace Information
7121 Standard Drive
Hanover, MD 21076



Jet Noise Predictions Based on Two Different Forms of Lilley's Equation

Part 1: Basic Theory

Marvin E. Goldstein
Glenn Research Center, Cleveland, Ohio

Abbas Khavaran
QSS Group, Inc., Cleveland, Ohio

Ricardo E. Musafir
Federal University of Rio de Janeiro, Rio de Janeiro, Brazil

Prepared for the
34th International Congress and Exposition on Noise Control Engineering
cosponsored by CAPES, Isover, Ecophon, Eurocoustic, CertainTeed, 3M,
01dB-Metravib, and Embraer
Rio de Janeiro, Brazil, August 7–10, 2005

National Aeronautics and
Space Administration

Glenn Research Center

This report is a formal draft or working paper, intended to solicit comments and ideas from a technical peer group.

This report contains preliminary findings, subject to revision as analysis proceeds.

This report is a preprint of a paper intended for presentation at a conference. Because of changes that may be made before formal publication, this preprint is made available with the understanding that it will not be cited or reproduced without the permission of the author.

Available from

NASA Center for Aerospace Information
7121 Standard Drive
Hanover, MD 21076

National Technical Information Service
5285 Port Royal Road
Springfield, VA 22100

Available electronically at <http://gltrs.grc.nasa.gov>

Jet Noise Predictions Based on Two Different Forms of Lilley's Equation

Part 1: Basic Theory

Marvin E. Goldstein
National Aeronautics and Space Administration
Glenn Research Center
Cleveland, Ohio 44135

Abbas Khavaran
QSS Group, Inc.
Cleveland, Ohio 44135

Ricardo E. Musafir
Universidade Federal do Rio de Janeiro
Rio de Janeiro 21945-970, Brazil

Abstract

The far field acoustic spectra at 90° to the downstream axis of some typical high speed jets are calculated from two different forms of Lilley's equation combined with some recent measurements of the relevant turbulent source function. These measurements, which were limited to a single point in a low Mach number flow, were extended to other conditions with the aid of a highly developed RANS calculation. The results are compared with experimental data over a range of Mach numbers. Both forms of the analogy lead to predictions that are in fair agreement with the experimental data at subsonic Mach numbers. The agreement is not quite as good at supersonic speeds, but the data appears to be slightly contaminated by shock- associated noise in this case.

1. Introduction

The acoustic analogy introduced by Lighthill (ref. 1) over 50 years ago remains the principle tool for predicting the noise from high speed air jets. In its most general formulation, it amounts to rearranging the Navier-Stokes equations into a form that separates out the linear terms and associates them with propagation effects that can then be determined as part of the solution. The non-linear terms are treated as "known" source functions to be determined by modeling and, in more recent approaches, parameterized with the parameters being determined from a steady RANS calculation. The "base" flow (about which the linearization is carried out) is usually assumed to be parallel and the resulting equation is usually referred to as Lilley's (ref. 2) equation.

The major drawback with these approaches is that the unsteady effects, which actually generate the sound, must be included as part of the model. This clearly puts severe demands on the modeling aspects of the prediction, which usually amount to assuming a functional form for the two point time delayed velocity correlation spectra. These predictions should, however, be less sensitive to the details of the model when it is possible to neglect variations in retarded time across the source correlation volume. It is therefore fortunate that this seems to be a reasonable approximation when performed in an appropriate moving frame of reference (ref. 3). The source models are usually tested by comparing them with measurements of the far field acoustic spectrum at 90° to the downstream jet axis, which is believed to be uninfluenced by propagation effects. The main purpose of this paper is to show that this spectrum can be accurately predicted by using an appropriate acoustic analogy approach combined with some measurements of the source function that were recently carried out by Harper-Bourne (ref. 4).

2. The Acoustic Analogy Equation and its Far-Field Solution

Reference 5 shows that the Navier-Stokes equations can be rewritten (for an ideal gas) as the linearized Navier-Stokes (LNS) equations about a very general “base flow” but with different (in general non-linear) dependent variables, with the heat flux vector replaced by a generalized enthalpy flux and with the viscous stresses replaced by a generalized Reynolds stress. *This is a true acoustic analogy (in the Lighthill (ref. 1) sense) in that it shows that there is an exact analogy between the flow fluctuations in any real flow and the linear fluctuations about a very general “base flow” due to an externally imposed “viscous” stress and “heat flux” vector.*

When the “base” flow is taken to be the unidirectional transversely sheared mean flow

$$v_i = \delta_{i1} U(x_2, x_3), \rho = \bar{\rho}(x_2, x_3), p = \bar{p} = \text{constant} \quad (1)$$

where $\mathbf{x} = \{x_1, x_2, x_3\}$ is a Cartesian coordinate system, $\mathbf{v} = \{v_1, v_2, v_3\}$ denotes the velocity, p the pressure and ρ the density, the resulting LNS equations can be combined to obtain the modified Lilley’s (ref. 1) equation

$$Lp'_e = \left(\frac{D}{Dt} \frac{\partial}{\partial x_i} \tilde{c}^2 - \frac{\partial U}{\partial x_i} 2\tilde{c}^2 \frac{\partial}{\partial x_1} \right) \frac{\partial e'_{ij}}{\partial x_j} - (\gamma - 1) \frac{D^2}{Dt^2} Q \quad (2)$$

where

$$L \equiv \frac{D}{Dt} \left(\frac{\partial}{\partial x_i} \tilde{c}^2 \frac{\partial}{\partial x_i} - \frac{D^2}{Dt^2} \right) - 2 \frac{\partial U}{\partial x_j} \frac{\partial}{\partial x_1} \tilde{c}^2 \frac{\partial}{\partial x_j} \quad (3)$$

is the variable-density Pridmore-Brown (ref. 17) operator

$$\tilde{c}^2 \equiv \gamma \bar{p} / \bar{\rho}(x_2, x_3) \quad (4)$$

is the square of the mean-flow sound speed, γ = the specific heat ratio, t denotes the time,

$$\frac{D}{Dt} \equiv \frac{\partial}{\partial t} + U \frac{\partial}{\partial x_1} \quad (5)$$

denotes the convective derivative based on U . The dependent variable p'_e and source strengths e'_{ij} and Q are given by

$$p'_e \equiv p' + \frac{\gamma - 1}{2} \rho v'^2 \quad (6a)$$

and

$$e'_{ij} \equiv -\rho v'_i v'_j + \frac{\gamma - 1}{2} \delta_{ij} \rho v'^2 + \sigma_{ij} \quad (7a)$$

$$Q \equiv \frac{\partial}{\partial x_j} \eta'_j + \frac{\partial U}{\partial x_j} e'_{1i} \quad (8a)$$

where

$$\eta'_i \equiv -\rho v'_i h'_0 - q_i + \sigma_{ij} v'_j \quad (9)$$

when the limiting form of the general equations are used directly. Here

$$v'_i \equiv v_i - \delta_{i1} U \quad (10)$$

$$h'_0 \equiv h' + \frac{1}{2} v'^2 \quad (11)$$

and $h' \equiv h - \frac{\widetilde{c^2}}{\gamma - 1}$, $h'_0 \equiv h' + \frac{v'^2}{2}$, with h being the enthalpy. The viscous stress and heat flux vector, σ_{ij}

and q_i respectively, are believed to play a negligible role in the sound generation process and will therefore be neglected in the following.

But the limiting form of the equations can also be rearranged to obtain a simpler result (ref. 19), which amounts to replacing the dependent variable p'_e and source strengths e'_{ij} and Q by

$$p'_e \equiv p' \quad (6b)$$

$$e'_{ij} \equiv -\rho v'_i v'_j \quad (7b)$$

and

$$Q \equiv -\frac{\partial}{\partial x_j} \rho v'_j h' + v'_j \frac{\partial p'}{\partial x_j} \quad (8b)$$

in the inviscid limit. *These results are exact consequences of the Navier-Stokes (inviscid Navier-Stokes) equations, but it is* frequently argued that the fluctuating enthalpy flux η'_i , which appears in the first formulation (and correspond to the isentropic part of the pressure density source in the Lighthill approach (ref. 1)) is only important for hot jets (refs. 2, 6 to 8) except, perhaps, at small angles to the downstream jet axis (ref. 9) Similar arguments would suggest that the enthalpy fluctuation term that appears in the second formulation is also unimportant in cold jets and since it can be shown that the ideal gas law implies

$$p' = \frac{\gamma - 1}{\gamma} \rho h' + \frac{\rho}{\gamma} \widetilde{c^2} \quad (12)$$

it would seem that the second member in (8b) would also be negligible as well. We therefore neglect these terms in the present study. The main difference between these two formulations is then the dipole-

like term $\frac{\partial U}{\partial x_i} (\gamma - 1) \frac{D^2}{Dt^2} e'_{1i}$ that appears in the first formulation, but not in the second. Since both

formulations are initially exact consequences of the Navier-Stokes (inviscid Navier-Stokes) equations, any differences in the resulting acoustic predictions must be attributable to the introduction of these approximations and this research was initially undertaken as an attempt to distinguish between the two.

In either case, the generalized Lilley's equation can be solved (ref. 10) in terms of the free space Greens' function (ref. 18) $G(\mathbf{x}, t | \mathbf{y}, \tau)$, which satisfies

$$LG(\mathbf{x}, t | \mathbf{y}, \tau) = \delta(\mathbf{x} - \mathbf{y})\delta(t - \tau) \quad (13)$$

and has outgoing wave behavior at infinity, to obtain the following expression

$$\overline{p^2(\mathbf{x}, t)} = \int_{-\infty}^{\infty} \int_V \bar{\gamma}_{ijkl}(\mathbf{x} | \mathbf{y}; \boldsymbol{\xi} + \hat{\mathbf{i}} U_c \tau, t + \tau) R_{ijkl}^M(\mathbf{y}; \boldsymbol{\xi}, \tau) d\mathbf{y} d\boldsymbol{\xi} d\tau \quad (14)$$

for the pressure autocovariance (ref. 22) (notice that *the p_e' in the first formulation* reduces to p' in the far field)

$$\overline{p^2(\mathbf{x}, t)} \equiv \frac{1}{2T} \int_{-T}^T p_e'(\mathbf{x}, t_0) p_e'(\mathbf{x}, t_0 + t) dt_0 \quad (15)$$

where V denotes integration over all space, T denotes some large but finite time interval.

$$\bar{\gamma}_{ijkl}(\mathbf{x} | \mathbf{y}; \boldsymbol{\eta}, t + \tau) \equiv \int_{-\infty}^{\infty} \gamma_{ij}(\mathbf{x}, \mathbf{y}, t_1 + t + \tau) \gamma_{kl}(\mathbf{x} | \mathbf{y} + \boldsymbol{\eta}, t_1) dt_1 \quad (16)$$

where the propagation factor $\gamma_{kl}(\mathbf{x} | \mathbf{y}, t)$ is defined in reference 10. $R_{ijkl}^M(\mathbf{y}; \boldsymbol{\xi}, \tau)$ is a moving frame correlation tensor, which is defined in terms of the fixed frame density-weighted, fourth-order, two-point, time-delayed fluctuating velocity correlation (with the indicated arguments referring to all three terms preceding the parentheses)

$$R_{ijkl}(\mathbf{y}; \boldsymbol{\eta}, \tau) \equiv \frac{1}{2T} \int_{-T}^T \rho v_i' v_j'(\mathbf{y}, \tau_0) \rho v_k' v_l'(\mathbf{y} + \boldsymbol{\eta}, \tau_0 + \tau) d\tau_0 \quad (17)$$

and the second order fixed frame density weighted correlation

$$R_{ij}(\mathbf{y}; \boldsymbol{\eta}, \tau) \equiv \frac{1}{2T} \int_{-T}^T \sqrt{\rho} v_i'(\mathbf{y}, \tau_0) \sqrt{\rho} v_j'(\mathbf{y} + \boldsymbol{\eta}, \tau_0 + \tau) d\tau_0 \quad (18)$$

by

$$R_{ijkl}^M(\mathbf{y}; \boldsymbol{\xi}, \tau_0) \equiv R_{ijkl}(\mathbf{y}; \boldsymbol{\xi} + \hat{\mathbf{i}} U_c \tau, \tau) - R_{ij}(\mathbf{y}; \mathbf{0}, 0) R_{kl}(\mathbf{y} + \boldsymbol{\xi} + \hat{\mathbf{i}} U_c \tau; \mathbf{0}, 0) \quad (19)$$

where

$$\xi \equiv \eta - \hat{\mathbf{i}} U_c \tau \quad (20)$$

denotes a moving frame coordinate system, with U_c being the convection velocity of the turbulence.
Our interest is in the far field spectrum

$$I_\omega(\mathbf{x}) \equiv \frac{1}{2\pi} \int_{-\infty}^{\infty} e^{i\omega t} \overline{p^2}(\mathbf{x}, t) dt \quad (21)$$

which can be calculated by taking the Fourier transform of eq. (14) and using the convolution theorem (ref. 18) to obtain

$$I_\omega(\mathbf{x}|\mathbf{y}) = 2\pi \int_{-\infty}^{\infty} \int_V \Gamma_{ij}(\mathbf{x}|\mathbf{y}; \omega) \Gamma_{kl}^*(\mathbf{x}|\mathbf{y} + \xi + \hat{\mathbf{i}} U_c \tau; \omega) e^{-i\omega \tau} R_{ijkl}^M(\mathbf{y}, \xi, \tau) d\xi d\tau \quad (22)$$

where

$$\Gamma_{ij} \equiv \frac{1}{2\pi} \int_{-\infty}^{\infty} e^{i\omega(t-\tau)} \gamma_{ij}(\mathbf{x}|\mathbf{y}, t-\tau) d(t-\tau) \quad (23)$$

is the Fourier transform of γ_{ij} (we use capital letters to denote Fourier transform of the corresponding lower case quantity) and we introduced $I_\omega(\mathbf{x}|\mathbf{y})$, the acoustic spectrum at \mathbf{x} due to a unit volume of turbulence at \mathbf{y} , i.e.,

$$I_\omega(\mathbf{x}) = \int_V I_\omega(\mathbf{x}|\mathbf{y}) d\mathbf{y} \quad (24)$$

in order to simplify the formulas. The relevant far field expansion of Γ_{ij} is given in reference 10.

The only approximations made up to this point is the neglect of the enthalpy and viscous source terms, but equation (22) will depend on the turbulent source correlations only through

$$\mathcal{R}_{ijkl}(\mathbf{y}, \tau) \equiv \int_V R_{ijkl}^M(\mathbf{y}, \xi, \tau) d\xi \quad (25)$$

if variations in retarded time across the correlation volume are neglected, i.e., if $\Gamma_{kl}^*(\mathbf{x}|\mathbf{y} + \xi + \hat{\mathbf{i}} U_c \tau; \omega)$ is assumed to be constant over the correlation volume (ref. 3). However, the definitions (15) and (19) imply that the integration variable in equation (25) can be changed back to η , which means that

$$\mathcal{R}_{ijkl}(\mathbf{y}, \tau) \equiv \int_V [R_{ijkl}(\mathbf{y}, \eta, \tau) - R_{ij}(\mathbf{y}; \mathbf{0}, 0) R_{kl}(\mathbf{y} + \eta; \mathbf{0}, 0)] d\eta \quad (26)$$

Equation (22) can now be written more simply as

$$I_{\omega}(\mathbf{x}|\mathbf{y}) \rightarrow \left(\frac{2\pi}{x}\right)^2 \frac{2\pi\omega}{c_{\infty}} \sin\theta \bar{\Gamma}_{ij}(\mathbf{x}|\mathbf{y}_{\perp}) \bar{\Gamma}_{kl}^*(\mathbf{x}|\mathbf{y}_{\perp}) \Phi_{ijkl}^*(\mathbf{y}; \omega(1 - M_c \cos\theta)) \quad (27)$$

as $x \rightarrow \infty$

where

$$\Phi_{ijkl}(\mathbf{y}, \omega) \equiv \frac{1}{2\pi} \int_{-\infty}^{\infty} e^{i\omega\tau} \mathcal{R}_{ijkl}(\mathbf{y}, \tau) d\tau \quad (28)$$

is the spectral tensor of the source correlation and

$$M_c \equiv U_c / c_{\infty} \quad (29)$$

is the convective Mach number of the turbulence. This result shows that it is only necessary to model the overall spectral tensor itself and not the detailed two-point time delayed correlations of the turbulence. However, the radiated sound should still be relatively insensitive to the detailed turbulence structure even when the latter quantities are modeled (as is at least partially done below). This would not be the case if the moving frame had not been introduced before neglecting the retarded time variations (ref. 3).

For reasons given in the introduction, our interest here is in the spectrum at 90° to the jet axis where $\cos\theta = 0$. We only carry out the analysis for the first formulation and simply give the final result for the second (for reasons that will become clear when that is actually done). Reference 10 shows that

$$I_{\omega}(\mathbf{x}|\mathbf{y}) = \frac{(\omega/c_{\infty})^4}{(4\pi x)^2} \left[\frac{x_i x_j}{x^2} - \frac{\gamma-1}{2} \delta_{ij} + \frac{i(\gamma-1)\delta_{li}}{\omega} \frac{\partial U}{\partial y_j} \right] \left[\frac{x_k x_l}{x^2} - \frac{\gamma-1}{2} \delta_{kl} - \frac{i(\gamma-1)\delta_{lk}}{\omega} \frac{\partial U}{\partial y_l} \right] \Phi_{ijkl}^*(\mathbf{y}; \omega) \quad \text{for } \theta = \pi/2. \quad (30)$$

when $\widetilde{c_0^2} = c_{\infty}^2 = \text{constant}$, i.e., in the isothermal case.

3. The Quasi-Normal and Axisymmetric Turbulence Approximations

To proceed further, we need to know something about the source spectral tensor Φ_{ijkl} . The usual approach (refs. 12, 13, and 3) is to begin by assuming that the turbulence is quasi-normal (ref. 16) (see ref. 10) in order to obtain some relations among its components. It then follows that (see comments preceding equation (20))

$$\begin{aligned} R_{ijkl}(\mathbf{y}, \boldsymbol{\eta}, \tau) - R_{ij}(\mathbf{y}, \mathbf{0}, 0) R_{kl}(\mathbf{y} + \boldsymbol{\eta}, \mathbf{0}, 0) &= R_{ik}(\mathbf{y}, \boldsymbol{\eta}, \tau) R_{jl}(\mathbf{y}, \boldsymbol{\eta}, \tau) \\ &+ R_{il}(\mathbf{y}, \boldsymbol{\eta}, \tau) R_{jk}(\mathbf{y}, \boldsymbol{\eta}, \tau) \end{aligned} \quad (31)$$

To further reduce the number of independent components it is usual to assume some kinematically possible symmetric form for the second order correlations. Early studies (ref. 20) assumed the turbulence to be isotropic, but that turns out to be incompatible with the Harper-Bourne (ref. 17) measurements (to be introduced below). The simplest assumption compatible with his results is the one introduced in references 12 and 13, namely that the turbulence is axisymmetric, which implies that (ref. 16)

$$R_{ij}(\mathbf{y}; \boldsymbol{\eta}, \tau) = A_0 \eta_i \eta_j + B_0 \delta_{ij} + C_0 \delta_{1i} \delta_{1j} + D_0 (\delta_{1j} \eta_j + \delta_{1i} \eta_i) \quad (32)$$

where A_0 , B_0 , C_0 , and D_0 are functions of \mathbf{y} , τ_0 , and η_\perp ; A_0 , B_0 , and C_0 are even functions η_\perp and D_0 is an odd function of this quantity. This model is chosen because it is the most general of those whose mathematical properties have been studied in the literature and because it reflects the fact that the cross flow velocity components tend to be much more similar to one another than to the stream-wise component—even for non-axisymmetric flows. Inserting equation (32) into equation (31) and inserting the result into equation (30) via equations (28) and (26) yields (after a straight forward but tedious calculation that follows along the lines of the one in appendix A of reference 12)

$$I_\omega(\mathbf{x}|\mathbf{y})(4\pi x)^2 = 2\left(\frac{\omega}{c_\infty}\right)^4 \left[\Phi_1 - (\gamma - 1)\Phi_2 + \left(\frac{\gamma - 1}{2}\right)^2 \Phi_3 \right] + \left[(\gamma - 1)\frac{\omega}{c_\infty} |\nabla M| \right]^2 \Phi_4 \quad (33)$$

where

$$\Phi_1 \equiv \frac{1}{2\pi} \int_{-\infty}^{\infty} e^{-i\omega\tau} \int_V R_{22}^2(\mathbf{y}, \boldsymbol{\eta}, \tau) d\boldsymbol{\eta} d\tau \quad (34a)$$

$$\Phi_2 \equiv \frac{1}{2\pi} \int_{-\infty}^{\infty} e^{-i\omega\tau} \int_V (R_{23}^2 + R_{12}^2 + R_{22}^2) d\boldsymbol{\eta} d\tau \quad (34b)$$

$$\Phi_3 \equiv \frac{1}{2\pi} \int_{-\infty}^{\infty} e^{-i\omega\tau} \int_V (4R_{12}^2 + 2R_{23}^2 + R_{11}^2 + 2R_{22}^2) d\boldsymbol{\eta} d\tau \quad (34c)$$

and

$$\Phi_4 \equiv \frac{1}{2\pi} \int_{-\infty}^{\infty} e^{-i\omega\tau} \int_V (R_{12}^2 + R_{11}R_{22}) d\boldsymbol{\eta} d\tau \quad (34d)$$

are seemingly independent spectral functions. However, when compressibility effects are neglected (i.e., when ρ is treated as a constant) the coefficients A_0 , B_0 , C_0 , and D_0 are not all independent, but can be expressed in terms of two independent scalar functions of \mathbf{y} , τ_0 , η_\perp , and η_1 , say a and b (refs. 14 to 16), which scale like

$$b = \widetilde{\rho u_1^2} B(\tilde{\eta}_\perp, \tilde{\eta}_1) L_\perp^2 / 2 \quad (35)$$

and

$$g \equiv a - b_{\eta_1 \eta_1} = \widetilde{\rho u_2^2} D(\tilde{\eta}_\perp, \tilde{\eta}_1) \quad (36)$$

where

$$\tilde{\eta}_{\parallel} \equiv \eta_{\parallel} / L_{\parallel} \quad (37)$$

$$\tilde{\eta}_{\perp} \equiv \eta_{\perp} / L_{\perp} \quad (38)$$

L_{\parallel} and L_{\perp} denote characteristic stream-wise and transverse length scales of the turbulence, and B and D are $O(1)$ functions of the indicated arguments.

Turbulence measurements suggest

$$\varepsilon \equiv \frac{L_{\perp}}{4L_{\parallel}} \quad (39)$$

ought to be small. In fact, Harper-Bourne's (ref. 17) measurements (to be discussed below) suggest that $\varepsilon \approx 2.7 \times 10^{-2}$.

Reference 10 shows that

$$\frac{\left(\frac{4}{3}\right)\Phi_1}{2\pi L_{\parallel} L_{\perp}^2 \left(\widetilde{\rho u_{\parallel}^2}\right)^2} = \frac{\Phi_2}{2\pi L_{\parallel} L_{\perp}^2 \left(\widetilde{\rho u_{\parallel}^2}\right)^2} = r^2 \int_{-\infty}^{\infty} e^{-i\omega\tau} \int_{-\infty}^{\infty} \int_0^{\infty} \left(\tilde{\eta}_{\perp} \frac{\partial D}{\partial \tilde{\eta}_{\perp}} \right)^2 \tilde{\eta}_{\perp} d\tilde{\eta}_{\perp} d\tilde{\eta}_{\parallel} d\tau \quad (40a,b)$$

$$\frac{\Phi_3}{2\pi L_{\parallel} L_{\perp}^2 \left(\widetilde{\rho u_{\parallel}^2}\right)^2} = \int_{-\infty}^{\infty} e^{-i\omega\tau} \int_{-\infty}^{\infty} \int_0^{\infty} \left[\frac{\bar{B}^2}{8} + 2r^2 \left(\tilde{\eta}_{\perp} \frac{\partial D}{\partial \tilde{\eta}_{\perp}} \right)^2 \right] \tilde{\eta}_{\perp} d\tilde{\eta}_{\perp} d\tilde{\eta}_{\parallel} d\tau \quad (40c)$$

$$\frac{\Phi_4}{2\pi L_{\parallel} L_{\perp}^2 \left(\widetilde{\rho u_{\parallel}^2}\right)^2} = \frac{r}{2} \int_{-\infty}^{\infty} e^{-i\omega\tau} \int_{-\infty}^{\infty} \int_0^{\infty} \bar{B} \left(\frac{\partial}{\partial \tilde{\eta}_{\perp}} \tilde{\eta}_{\perp}^2 D \right) d\tilde{\eta}_{\perp} d\tilde{\eta}_{\parallel} d\tau \quad (40d)$$

when $O(\varepsilon^2)$ terms are neglected-the ratio r is defined by

$$r \equiv \widetilde{\rho u_{\perp}^2} / \widetilde{\rho u_{\parallel}^2} \quad (41)$$

Lacking any specific data to the contrary, it seems reasonable to suppose that

$$(\Gamma\bar{r})^2 = \frac{1}{\pi} \int_{-\infty}^{\infty} e^{-i\omega\tau} \int_V R_{22}^2(y, \mathbf{\eta}, \tau) d\mathbf{\eta} d\tau / \Phi_0 \quad (42)$$

where

$$\Phi_0 \equiv \frac{1}{\pi} \int_{-\infty}^{\infty} e^{-i\omega\tau} \int_V R_{11}^2(y, \mathbf{\eta}, \tau) d\mathbf{\eta} d\tau = \int_V H_0(y, \mathbf{\eta}, \tau) d\mathbf{\eta} \quad (43)$$

is a constant, i.e., independent of ω and source location y . Equation (31) then becomes

$$I_{\omega}(\mathbf{x}|\mathbf{y})(2\pi x c_{\infty})^2 = C_0^2 \Phi_o(\mathbf{y}, \omega) \left(\frac{\omega}{c_{\infty}} \right)^2 \left[\omega^2 + (\kappa |\nabla U|)^2 \right] \quad (44)$$

where

$$2C_0^2 \equiv \frac{2}{3}(\Gamma \bar{r})^2 \left[\frac{3}{4} - (\gamma - 1) + 2 \left(\frac{\gamma - 1}{2} \right)^2 \right] + \frac{1}{2} \left(\frac{\gamma - 1}{2} \right)^2 \quad (45)$$

is a constant and

$$\kappa \equiv \left(\frac{\gamma - 1}{2} \right) \frac{1}{C_0} \sqrt{\frac{2\bar{r} \int_{-\infty}^{\infty} e^{-i\omega\tau_0} \int_{-\infty}^{\infty} \int_0^{\infty} \bar{B} \left(\frac{\partial}{\partial \tilde{\eta}_{\perp}} \tilde{\eta}_{\perp}^2 D \right) d\tilde{\eta}_{\perp} d\tilde{\eta}_{\parallel} d\tau}{\int_{-\infty}^{\infty} e^{-i\omega\tau_0} \int_{-\infty}^{\infty} \int_0^{\infty} \bar{B}^2 \tilde{\eta}_{\perp} d\tilde{\eta}_{\perp} d\tilde{\eta}_{\parallel} d\tau}} \quad (46)$$

References

1. Lighthill, M.J., "On Sound Generated Aerodynamically: I. General Theory," *Proceedings R. Society Lond.*, A 211, 1952, pp. 564–587
2. Lilley, G.M., "On the Noise from Jets," Noise Mechanism, AGARD-CP-131
3. Ffowcs, William, J.E., "The Noise from Turbulence Convected at High Speed," *Phil. Trans. Roy. Soc.*, A 225, 1963, pp. 469–503
4. Harper-Bourne, M., "Jet Noise Turbulence Measurements," AIAA Paper 2003-3214, 2003.
5. Goldstein, M.E., "A Generalized Acoustic Analogy," *Journal of Fluid Mechanics*, vol. 488, 2003, pp. 315–333.
6. Lilley, G.M., "The Radiated Noise from Isotropic Turbulence with Applications to the Theory of Jet Noise," *Journal of Sound and Vibration*, vol. 190, 1996, pp. 463–476.
7. Morfey, C.L., Szewczyk, V.M., and Fisher, B.J., "New Scaling Laws for Hot and Cold Jet Mixing Noise Based on a Geometric Acoustics Model," *Journal of Sound and Vibration*, vol. 46, no. 1, 1976, pp. 79–103.
8. Lilley, G.M., "Jet Noise: Classical Theory and Experiments" in *Aeroacoustics of Flight Vehicles*, H. Hubbard ed., vol. 1 NASA RP-1258, and WRDC TR-90-3052, 1991, pp. 211–289
9. Freund, J.B., "Turbulent Jet Noise: Shear Noise, Self-Noise, and Other Contributions," AIAA Paper 2002-2423, 2002.
10. Goldstein, M.E., "The 90° Acoustic Spectrum of a High Speed Air Jet," *AIAA Journal*, vol. 42, no. 11, Nov. 2004.
11. Goldstein, M.E. and Rosenbaum, B.M., "Emission of Sound from Turbulence Converted by a Parallel Flow in the Presence of Solid Boundaries," NASA TN D-7118, 1973.
12. Goldstein, M.E. and Rosenbaum, B., "Effect of Anisotropic Turbulence on Aerodynamic Noise," *Journal of the Acoustical Society of America*, vol. 54, no. 3, 1973, pp. 630–645.
13. Kerschen, E.J., "Constraints on the Invariant Function of Axisymmetric Turbulence," *AIAA Journal*, vol. 21, no. 7, 1983, pp. 978–985.

14. Lindborg, E., "Kinematics of Homogeneous Axisymmetric Turbulence," *Journal of Fluid Mechanics*, vol. 302, 1995, pp. 179–201.
15. Khavaran, A., "Role of Anisotropy in Turbulent Mixing Noise," *AIAA Journal*, vol. 37, no. 7, 1999, pp. 832–841
16. Batchelor, G.K., "Theory of Homogeneous Turbulence," Cambridge University Press, 1953.
17. Pridmore-Brown, "Sound Propagation in a Fluid Flowing Through an Attenuating Duct," *Journal of Fluid Mechanics*, vol. 4, 1958, pp. 393–406.
18. Morse, P.M. and Feshbach, H., "Methods of Theoretical Physics," McGraw-Hill, 1953.
19. Musafir, R.E. Submitted to *Acta Acustica*.
20. Ribner, H.E., "The Generation of Sound by Turbulent Jets," *Advances in Applied Mechanics*, vol. 8, Academic Press, New York, 1964, pp.104–182.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE September 2005		3. REPORT TYPE AND DATES COVERED Technical Memorandum
4. TITLE AND SUBTITLE Jet Noise Predictions Based on Two Different Forms of Lilley's Equation Part 1: Basic Theory			5. FUNDING NUMBERS Cost Center 2250000002	
6. AUTHOR(S) Marvin E. Goldstein, Abbas Khavaran, and Ricardo E. Musafir				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration John H. Glenn Research Center at Lewis Field Cleveland, Ohio 44135-3191			8. PERFORMING ORGANIZATION REPORT NUMBER E-15199-1	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration Washington, DC 20546-0001			10. SPONSORING/MONITORING AGENCY REPORT NUMBER NASA TM-2005-213829-PART1	
11. SUPPLEMENTARY NOTES Prepared for the 34th International Congress and Exposition on Noise Control Engineering cosponsored by CAPES, Isover, Ecophon, Eurocoustic, CertainTeed, 3M, 01dB-Metravib, and Embraer, Rio de Janeiro, Brazil, August 7-10, 2005. Marvin E. Goldstein, NASA Glenn Research Center; Abbas Khavaran, QSS Group, Inc., 21000 Brookpark Road, Cleveland, Ohio 44135; and Ricardo E. Musafir, Federal University of Rio de Janeiro, Rio de Janeiro, Brazil. Responsible person, Marvin E. Goldstein, organization code RO, 216-433-5825.				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Unclassified - Unlimited Subject Category: 71 Available electronically at http://gltrs.grc.nasa.gov This publication is available from the NASA Center for AeroSpace Information, 301-621-0390.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) The far field acoustic spectra at 90° to the downstream axis of some typical high speed jets are calculated from two different forms of Lilley's equation combined with some recent measurements of the relevant turbulent source function. These measurements, which were limited to a single point in a low Mach number flow, were extended to other conditions with the aid of a highly developed RANS calculation. The results are compared with experimental data over a range of Mach numbers. Both forms of the analogy lead to predictions that are in fair agreement with the experimental data at subsonic Mach numbers. The agreement is not quite as good at supersonic speeds, but the data appears to be slightly contaminated by shock-associated noise in this case.				
14. SUBJECT TERMS Aeroacoustics			15. NUMBER OF PAGES 16	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT	

